

Hi-Coat Gloss Protect W988

Characteristics: W988 is a medium fast drying coating with good gloss results and high transparency. W988 is giving excellent water and wet rub resistance. W988 is especially adapted for label application and can be used as primer for later bronzing. Two layers of W988 will increase the water resistance significant.

Application:

- Application weight 4-6 g/m² (wet-on-wet)
- adapted for board , paper, cast coated paper and metallized papers
- adapted for single and double side applications
- adapted for conventional coating units (Anilox/2 Roller systems)
- very good water resistance

Performance:

Gloss	+++
Matt	-
Block resistance	+++
Glueability	●
Slip	+++
Drying speed	+++
Double sided applications	●
Rub resistance	+++

+ = low/slow +++ = very high/very fast ○ limited, test required ● suitable - not suitable

General advice: Use alkali and solvent resistant inks.
Circulate or stir well prior to using

Thinning: Reduce viscosity with water, if required.

Cleaning: Initial wash-up, use Hi-Clean W 020 wash diluted with cold water. Dried coating can be removed using neat Hi-Clean W 020 wash.

Storage: Protect from frost and excessive heat. Store in closed packaging.

Shelf life: 12 Month in original packaging.

Typical constants:

Appearance:	Opaque liquid	
Solids:	35%	± 4 %
Viscosity:	45 Sec. DIN 4 @ 20°C	± 4 Sek
Specific gravity:	1.04 g/cm ³	± 0.04

This technical data sheet is to inform and advice our customers. The successful application depends on variety of different factors which are beyond our control. We therefore ask for your understanding that these advice documents cannot be used as the basis for claims in law.